



www.cooled.com.tw



LED Floodlight

APPLICATIONS:
Billboard, Landscape, Outdoor Lighting etc.



LED Floodlight(DC)

Model : FD035 / FD100 / FD200



Part No.	FD035C-121	FD035W-121	FD035C-241	FD035W-241	FD035C-481	FD035W-481
Rated Lumen	3500 lm					
Rated Voltage	9-18 VDC		18-32 VDC		42-56 VDC	
Lighting Efficacy	140 lm/W					
Rated Power	25W					
Central lux@(1M/2M/3M)	1430Lx / 358Lx / 158Lx					
Color Temp	5000K	3000K	5000K	3000K	5000K	3000K
CRI	>80, R9>0					
Dimension(±2mm)	203mm(L) x 176mm(W) x 64mm(H)					
Weight(±5%)	1260g					

Part No.	FD100C-121	FD100W-121	FD100C-241	FD100W-241	FD100C-481	FD100W-481
Rated Lumen	10000 lm				9500 lm	
Rated Voltage	9-18 VDC		18-32 VDC		42-56 VDC	
Lighting Efficacy	125 lm/ W					
Rated Power	80W				76W	
Central lux@(1M/2M/3M)	3900Lx / 975Lx / 433Lx				3705Lx / 927Lx / 412Lx	
Color Temp	5000K	3000K	5000K	3000K	5000K	3000K
CRI	>80, R9>0					
Dimension(±2mm)	282mm(L) x 220mm(W) x 113mm(H)					
Weight(±5%)	2360g					

Part No.	FD200C-121	FD200W-121	FD200C-241	FD200W-241	FD200C-481	FD200W-481
Rated Lumen	20000 lm				19000 lm	
Rated Voltage	9-18 VDC		18-32 VDC		42-56 VDC	
Lighting Efficacy	125 lm/ W					
Rated Power	160W				152W	
Central lux@(1M/2M/3M)	7800Lx / 1950Lx / 866Lx				7410Lx / 1853Lx / 823Lx	
Color Temp	5000K	3000K	5000K	3000K	5000K	3000K
CRI	>80, R9>0					
Dimension(±2mm)	365mm(L) x 298mm(W) x 187mm(H)					
Weight(±5%)	6850g					